

800ML FIREBLOCK EXTINGUISHING GEL FOAM AEROSOL DATA SHEET

PRODUCT SPECIFICATION

MODEL:	FBGF-AEROSOL
CAPACITY:	800ML
MEDIUM:	FIREBLOCK GEL FOAM
DISCHARGE THROW:	2 METRES AT START OF DISCHARGE
PROPELLANT:	NITROGEN
FILLED WEIGHT:	± 970g
DISCHARGE TIME:	15 - 20 sec
WORKING PRESSURE:	10 BAR @ 20°C
TEST PRESSURE:	18 BAR
OPERATING TEMPERATURE:	5°C to 60°C
CYLINDER MATERIAL:	LINED ALUMINIUM
VALVE FINISH:	POLYPROPYLENE
PACKING SPEC (HXWXD):	330mm x 74mm x 74mm

PRODUCT DETAILS

1. VALVE
2. SAFETY PIN
3. TRIGGER
4. CYLINDER



TYPICAL RISKS



NOTE:

This product is intended only for use on small fires and as a first-aid measure. It is not a substitute for a certified fire extinguisher.

PRODUCED IN SOUTH AFRICA

Use only as directed. See instructions. T&Cs apply.

REV: 1



330mm - height

74mm - width

Specification subject to change without notice.
The image shown is for illustrative purposes only;
the actual product may vary in appearance and details.

www.fireblock.co.za